

Duralume®

Terms & Conditions of Warranty (Residential and Commercial)

1. This warranty is issued according to information supplied to Kiwi Steel.
2. Environmental Classifications are as described in the table below. The warranty shall not apply if the environment described herein is not an accurate assessment of the actual site details.
3. Maintenance must be carried out in accordance with the maintenance schedule
4. The product must be processed, installed and maintained in accordance with manufacturer's published literature, Kiwi Steel' literature and accepted good trade practice.
5. The products must be sold as prime material.
6. Garage doors are not included in this warranty.
7. Damage or corrosion resulting from the following are not covered by this warranty:
 - Mechanical, chemical, heat or wet storage damages.
 - Contact with or run off from dissimilar metals such as stainless steel, lead or copper.
 - Contact with or run off from corrosive materials such as fertiliser or wet concrete.
 - Exposed soffits or aggressive internal environments,
 - Storm, volcanic activity or other causes beyond the control of the roofing manufacturer.
8. Slopes down to 1 degree may be covered subject to the supporting structure, workmanship and associated works all being true and accurate, not permitting any accumulation of water, run-off, debris etc. at all time.
9. Kiwi Steel reserve the right to inspect a building prior to issuing of the warranty and/or to inspect and conduct tests at any time after a claim is made.
10. Installation on ISO 4 or 5, or any other identified severe environmental area, this warranty is void.

If the product has failed to perform as warranted, Kiwi steel will at its own option repair or replace the affected material. A new warranty shall be issued to cover the balance of the original offer for perforation protection.

Kiwi Steel shall not be liable for any consequential loss or damages except as may be required by law.


Maintenance Schedule

APPLICATIONS	WARRANTIES	MAINTENANCE
Roofing	15 Years	Rain washing
Wall cladding	15 Years	Rain washing plus manual washing every 6 months.
Gutters/downpipes	10 Years	Manual washing every 3 months.
Fascia	10 Years	Manual washing every 3 months.

Environmental Classifications

Category	Characterised by	Typical Zones
Extreme Marine	Heavy salt deposits. Almost constants smell of salt spray in air	Within 50 Meters from breaking surf on East Coast, and 100 metres from breaking surf on West Coast.
Very Severe Marine	Heavy salt deposits. Almost constants smell of salt spray in air	Within 50-100 metres from breaking surf on east coast, 100-200 metres from breaking surf on West Coast.
Severe Marine	Light salt deposits. Frequent smell of salt in the air.	Commencing from Very Severe zone up to 500 metres or more inland from breaking surf; or in the immediate vicinity of calm salt water such as harbour foreshores.
Moderate Marine	Little or no salt deposits. Occasional smell of salt in the air.	500 metres to 1km from breaking surf; or in the immediate vicinity of calm salt water such as estuaries.
Moderate Inland	No obvious marine influences.	More than 1000 metres from salt water.

NOTE: Industrial and Geothermal areas subject to individual assessment.
The above terms are subject to correct design, storage, installation and maintenance provision

 , VITOR® and Vitor+ZX® are Registered Trademarks of Kiwi Steel NZ Ltd